



DATASHEET

FAST SWITCH

24 x 10/100Mbps PORTS

MODELLO: SW-UF24L-055

DESCRIPTION

The Fast Ethernet Switch provides 24 10/100Mbps Auto-Negotiation RJ45 ports. All ports support Auto MDI/MDIX function, eliminating the need for crossover cables or Uplink ports. The Switch is Plug-and-Play and each port can be used as general ports or Uplink ports and can be simply plugged into a server, a hub or a switch, using straight cable or crossover cable.

FEATURES

- Complies with IEEE802.3, IEEE802.3u standards.
- 24 10/100Mbps Auto-Negotiation RJ45 ports supporting Auto-MDI/MDIX.
- Supports IEEE802.3x flow control for Full Duplex mode and backpressure for half-duplex mode.
- Supports MAC address auto-learning and auto-aging.
- LED indicators for monitoring power, link, activity.
- 19" rack-mount mode Metal case
- Internal power supply 100~240VAC 50/60HZ
- Dimension: 440x180x44mm

SPECIFICATION

Interface	24 10/100/Mbps RJ45 Ports
	AUTO Negotiation/AUTO MDI/MDIX
Internal Power Supply	110~240V,50/60HZ
Transfer Method	Store and Forward
Advanced Functions	Green Technology saving power up to 70%
	802.3X Flow Control Back Pressure
	Auto-Uplink Every Port
Package Contents	24-Port 10/100Mbps rack-mount Switch
	Power Adapter cable
	User Guide
Environment	
Operating Temperature	0°C~40°C (32°F~104°F)
Storage Temperature	-40°C~70°C (-40°F~158°F)
Operating Humidity	10%~90% non-condensing
Storage Humidity	5%~90% non-condensing